



Nokian TRI 2

- Triumph on all grounds



Size	LI/SS	Recom- mend- ed rim	Allowed rims	Width mm/inch	Diameter mm/inch	Static radius ± 2.5% mm/inch	Rolling cir- cumference ± 2.5% mm/inch	Max inflation pressure kPa/psi	Load capacity kg / lb								Product no.
									30 km/h / 20 mph	40 km/h / 25 mph	50 km/h / 30 mph	65 km/h / 40 mph					
80-SERIES																	
250/80R16 ₁₎	119 G	W8	W7, 7J, 7.5J, 8J, 8.5J, W9, 9, 9.00, 9J	268 10,6	814 32,0	383 15,1	2 488 98,0	450 65	1 820	4 010	1 750	3 860	1 650	3 640	1 550	3 415	T845495
340/80R18	138 D	11	W10, W11, 12, W12	343 13,5	1 001 39,4	453 17,8	3 010 118,5	400 58	2 840	6 260	2 725	6 010	2 570	5 665	2 360	5 205	T445391
360/80R20	143 D	11	W10, W11, 12, W12	357 14,1	1 092 43,0	495 19,5	3 280 129,1	400 58	3 200	7 055	3 075	6 780	2 900	6 395	2 725	6 010	T445389
300/80R24	128 D	DW10	W9, W10, W11, DW11	295 11,6	1 090 42,9	499 19,6	3 292 129,6	320 46	2 150	4 740	2 060	4 540	1 940	4 275	1 800	3 970	T445419
340/80R24	135 D	DW11	W10, W11, W12, DW10, DW12	343 13,5	1 154 45,4	532 20,9	3 487 137,3	320 46	2 600	5 730	2 500	5 510	2 350	5 180	2 180	4 805	T445376
360/80R24	138 D	DW11	W10, W11, W12, W13, DW10, DW12, DW13	357 14,1	1 186 46,7	542 21,3	3 581 141,0	320 46	2 840	6 260	2 725	6 010	2 570	5 665	2 360	5 205	T445378
400/80R24	144 D	DW13	W12, W13, W14, DW12, DW14	404 15,9	1 250 49,2	568 22,4	3 764 148,2	320 46	3 380	7 450	3 250	7 165	3 060	6 745	2 800	6 175	T445372
440/80R24	149 D	DW14L	W15L, DW15L, W12, W13, W14L, DW12, DW14L	441 17,4	1 314 51,7	596 23,5	3 965 156,1	320 46	3 900	8 600	3 750	8 265	3 540	7 805	3 250	7 165	T445385
400/80R28	146 D	DW13	W12, W13, W14L, DW12, DW14L	404 15,9	1 351 53,2	620 24,4	4 090 161,0	320 46	3 600	7 935	3 450	7 605	3 260	7 185	3 000	6 615	T445383
440/80R28	151 D	DW14L	W15L, W16L, DW15L, DW16L	441 17,4	1 415 55,7	644 25,4	4 266 168,0	320 46	4 160	9 170	4 000	8 820	3 760	8 290	3 450	7 605	T445337
440/80R30	153 D	DW14L	DW15L, DW16L	441 17,4	1 466 57,7	670 26,4	4 430 174,4	320 46	4 300	9 480	4 125	9 095	3 880	8 555	3 650	8 045	T445384
480/80R30	157 D	DW15L	DW16L, DW18L	479 18,9	1 530 60,2	694 27,3	4 631 182,3	320 46	4 940	10 890	4 750	10 470	4 480	9 875	4 125	9 095	T445386
440/80R34	155 D	DW14L	DW15L, DW16L	441 17,4	1 568 61,7	717 28,2	4 750 187,0	320 46	4 560	10 055	4 375	9 645	4 120	9 085	3 875	8 545	T445369
480/80R34	159 D	DW15L	DW16L, DW18L	479 18,9	1 632 64,3	743 29,3	4 939 194,4	320 46	5 200	11 465	5 000	11 025	4 700	10 360	4 375	9 645	T445370
480/80R38	161 D	DW15L	DW16L, DW18L	479 18,9	1 733 68,2	793 31,2	5 265 207,3	320 46	5 520	12 170	5 300	11 685	5 000	11 025	4 625	10 195	T445377
540/80R38	167 D	DW18L	DW16L	550 21,7	1 829 72,0	834 32,8	5 529 217,7	320 46	6 600	14 550	6 300	13 890	5 940	13 095	5 450	12 015	T445338
620/80R42	177 D	DW20B	TW20B, DW21B, TW21B, DW23B, TW23B	625 24,6	2 059 81,1	934 36,8	6 262 246,5	320 46	8 600	18 960	8 250	18 190	7 800	17 195	7 300	16 095	T445518
75-SERIES																	
270/75R15 ₁₎	109 G	8.5J	7J, 7.5J, 8J, 8.5J, 9, 9.00, 9J, 9.5J	277 10,9	784 30,9	364 14,3	2 393 94,2	450 65	1 880	4 145	1 800	3 970	1 700	3 750	1 550	3 415	T845538
250/75R16 ₁₎	120 G	W8	W7, 7J, 7.5J, 8J, 8.5J, W9, 9, 9.00, 9J	258 10,2	782 30,8	363 14,3	2 390 94,1	450 65	1 720	3 790	1 650	3 640	1 560	3 440	1 450	3 195	T845539
70-SERIES																	
500/70R24	159 D	DW16L	DW15L, DW18L	503 19,8	1 310 51,6	585 23,0	3 958 155,8	400 58	5 200	11 465	5 000	11 025	4 700	10 360	4 375	9 645	T445467 (19.5LR24) ¹⁾
65-SERIES																	
420/65R24	146 D	DW13	W12, W13, W14L, DW12, DW14L, DW15L	418 16,5	1 156 45,5	525 20,7	3 493 137,5	400 58	3 600	7 935	3 450	7 605	3 260	7 185	3 000	6 615	T445392
460/65R24	151 D	DW14L	W15L, W16L, DW15L, DW16L	454 17,9	1 208 47,6	550 21,7	3 638 143,2	400 58	4 160	9 170	4 000	8 820	3 760	8 290	3 450	7 605	T445393
540/65R24	154 D	DW18L	DW16L	550 21,7	1 312 51,7	587 23,1	3 952 155,6	320 46	4 420	9 745	4 250	9 370	4 000	8 820	3 750	8 265	T445420
480/65R28	149 D	DW15L	DW14L, DW16L	479 18,9	1 335 52,6	604 23,8	4 040 159,1	320 46	3 900	8 600	3 750	8 265	3 540	7 805	3 250	7 165	T445444
540/65R28	155 D	DW18L	DW16L	550 21,7	1 413 55,6	641 25,2	4 273 168,2	320 46	4 680	10 320	4 500	9 920	4 240	9 350	3 875	8 545	T445442
540/65R30	156 D	DW18L	DW16L	550 21,7	1 464 57,6	667 26,3	4 417 173,9	320 46	4 820	10 625	4 625	10 195	4 360	9 610	4 000	8 820	T445371
600/65R38	166 D	DW18L	DW20B	591 23,3	1 745 68,7	790 31,1	5 290 208,3	320 46	6 250	13 780	6 000	13 230	5 640	12 435	5 300	11 685	T445445
650/65R38	170 D	DW20B	DW18L, DW23B	645 25,4	1 811 71,3	819 32,2	5 510 216,9	320 46	7 200	15 875	6 900	15 210	6 500	14 330	6 000	13 230	T445443
650/65R42	171 D	DW20A	DW18L, DW23A	645 25,4	1 913 75,3	873 34,4	5 799 228,3	320 46	7 400	16 315	7 100	15 655	6 700	14 770	6 150	13 560	T445390

Nokian Heavy Tyres Ltd.
Pirkkalaistie 7
P. O. Box 20
FI-37101 NOKIA, Finland

Tel. +358 10 401 7000
Fax +358 10 401 7318
heavytyres@nokiantyres.com
www.nokianheavytyres.com

Only purified,
low-aromatic oils are used
in our tyres' rubber compounds.



nokian®
HEAVY TYRES

Nokian TRI 2

- Triumph on all grounds



You and Nokian TRI 2

> *The most efficient contractor combo*

Today, the heavy machinery used for agricultural and contracting work faces tough demands. All day long, hour after hour, from field to gravel, from asphalt to ice. Practical tests grow tougher and increasingly versatile.

That suits us. Nokian TRI was the first block-patterned contracting tyre on the market, and its successor, Nokian TRI 2, is an even more durable and versatile tyre. Nokian TRI 2 is designed for hard use and tested in numerous test drives and tyre comparisons.

And time after time, test after test, Nokian TRI 2 comes out as the winner from challenges measuring economies, efficiency and durability.

Nokian TRI 2 is the most reliable tyre for hard contracting, all year round. From winners to winners.

Multiple test winner

The outcome of continuous research and development by Nokian Heavy Tyres, Nokian TRI 2 is your most economic choice for efficient hourly output. Numerous independent studies and Nokian Tyres' own tests speak an indisputable language about the superiority of Nokian TRI 2.

Durability and reliability

We test our tyres in extreme conditions in order to make sure that they overcome even the toughest challenges. The material and structure of Nokian TRI 2 are designed to guarantee high durability and even wearing.

Efficient and economical

Nokian TRI 2 has conquered numerous test drives calling for extreme grip, not only on test tracks or snow but also on fields and icy surfaces. In addition, Nokian TRI 2 has been superior in tests measuring fuel consumption.

Comfort and safety

Nokian TRI 2 provides very stable driving and safe mileage. The passenger car-like driving response adds comfort to on-road driving. The excellent driving response and quiet noise levels make work more pleasant.

> *Up to three times the service life of competing products.**

> *Up to 5 litres/h lower fuel consumption in comparison with competing products.**

> *For more information, see www.nokianheavytyres.com*

*Independent tyre test by MTT Agrifood Research Finland.

SUITABLE FOR VARIOUS JOBS

- Green area maintenance
- Silage manufacturing
- Spreading manure
- Spraying pesticides
- Baling hay
- Transporting grain
- General transportation
- Winter maintenance
- Road edge maintenance
- Soil cultivation
- Rental farming

